

P 产品介绍

Product Introduction


GPT300

400

P 产品特点

Product Features

- ◆ ±1.0%
- ◆
- ◆ Tin TiAIN
- ◆
- ◆ 0~ 35 to 0-2000bar / 0~ 500 to 0~ 30000psi
- ◆ 4~ 20mA 0~ 20mA 0~ 10v 0~ 5V
- ◆ 400
- ◆
- ◆ 1/2~ 20UNF M18*1.5, M22*1.5,



S 技术参数

Specification

项目	参数	
	0~ 35 to 2000bar(0~ 500 to 0~ 30000psi)	
	± 1% FS	
	± 0.8% FS	
	24VDC 9~ 36VDC	10 VDC 12 VDC
	4~ 20mA ,0~ 20mA , 0~ 10V,0~ 5V,1~ 5V	2.0mV/V for 5PIN, 3.33mV/V for 6PIN
	662°F (350)	
	752°F (400)	
	40 psi/100 0.3MPa/100	
	1/2-20 UNF (45°) M14x1.5,M18x1.5,M22x1.5 etc	
	1.5 x FSO	
	PSI, Bar, Mpa or Kg/cm ²	
	80% FSO	
	5PIN or 6PIN	
()	E,J,K,S type or Pt100	

T 产品选型 Type selection

GPT300	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	选型说明
A								
B								
C								
								0~ 5 to 200Mpa / 0~ 35 to 2000bar / 0~ 500 to 30000psi
		T1						4~ 20mA (
		T2						0~ 20mA (
		T3						0~ 10V (
		T4						0~ 5V (
		T5						1~ 5V (
		T6						2.0mV/V , 5PIN
		T7						3.33mV/V, 6PIN
		V1						24VDC (
		V2						9~ 36VDC (
		V3						10 VVDC
		V4						12 VVDC
		C1						1/2-1/2-20UNF
		C2						M14= M14*1.5
		C3						M18= M18*1.5
		B1						5 pin
		B2						6 pin
		L1						: 150mm
		L2						: 470mm
								J,K,E PT100